



PSD:2002



ASD:1001



APT:50



COAXIAL WOOFER AND DRIVER RECOMMENDED USE CHART

NOTE: All options listed below use our PXB2:2K5CX coax crossover.

Recommended Woofer	Recommended Comp. Driver	Recommended CD Polarity	PA Main	Floor Wedge	MI Use	Ceiling Mount*	Rated System Power (W) (Thermal)**
Beta 8CX	ASD-1001	Normal	OK	OK	Good	OK	250
Beta 8CX	PSD-2002-S8	Normal	OK	OK	OK	OK	250
Beta 8CX	APT-50/APT-3	Normal	NR	OK	Good	OK	200
Beta 10CX	ASD-1001	Normal	OK	Very Good	OK	OK	250
Beta 10CX	PSD-2002-S8	Normal	Good	Good	OK	OK	250
Beta 10CX	APT-50/APT-3	Normal	NR	NR	OK	OK	200
Beta 12CX	ASD-1001	Normal	Good	OK	OK	OK	250
Beta 12CX	ASD-1001	Reverse	OK	Very Good	NR	NR	250
Beta 12CX	PSD-2002-S8	Normal	Good	Good	OK	OK	250
Beta 12CX	APT-50/APT-3	Normal	NR	OK	OK	OK	200

*The Beta CX woofers will require a proper rear enclosure when used in the ceiling to realize their full potential.

**System Power is a thermal rating. Actual power handling will depend on the enclosure alignment and desired bandwidth.

VIEW OUR ENTIRE LINE OF LOUDSPEAKERS AND HF PRODUCTS AT WWW.EMINENCE.COM