

EMINENCE®  
Tour Grade Speaker

**NSW4018-8**

**18" Tour Grade - American Muscle**

Advanced FEA optimization tools were implemented on this next generation of touring grade worthy subwoofers by Eminence. The result is an extremely long throw, lightweight, and exceptionally high power handling driver with top notch performance in small to large vented enclosures.

**18" | 3200 W  
8 Ω**



- Midrange
- Woofer
- Sealed Box
- Scoop Loading
- Midbass
- Subwoofer
- Bass Guitar
- Vented Box
- Horn Loading

**SPECIFICATION**

Nominal Basket Diameter	18.0", 457 mm
Nominal Impedance*	8 Ω
Power Rating**	
Watts (AES)	1600 W
Music Program	3200 W
Peak Power	6400 W
Resonance	36 Hz
Usable Frequency Range	27 Hz - 1.3 kHz
Sensitivity***	96.6 dB
Magnet Weight	33 oz.
Gap Height	0.5", 12.7 mm
Voice Coil Diameter	4.0", 102 mm
Winding Height	1.60", 40.64 mm
Mirror Image Twin Spiders	
Water Resistant	

**THIELE SMALL PARAMETERS\***

Fs	36 Hz
Re	5.86 Ω
Le	1.54 mH
Qms	8.46
Qes	0.39
Qts	0.38
Vas	5.81 cu.ft., 164.49 liters
Vd	1851.1 cc
Cms	0.08 mm/N
BL	28.24 T-M
Mms	237 grams
EBP	91
Xmax	15.21 mm
Sd	1217.0 cm <sup>2</sup>
Xlim	31.5 mm

**MOUNTING INFORMATION**

Recommended Enclosure Volume	
Sealed	N/A - liters, N/A - cu.ft.
Vented	99.11 - 339.80 liters, 3.50 - 12.00 cu.ft.
Driver Volume Displaced	0.205 cu.ft., 5.81 liters
Overall Diameter	18.13", 460.5 mm
Baffle Hole Diameter	16.60", 421.6 mm
Front Sealing Gasket	Yes
Rear Sealing Gasket	Yes
Mounting Holes Diameter	0.28", 7.1 mm
Mounting Holes B.C.D.	17.32", 439.9 mm
Depth	8.90", 226.1 mm
Net Weight	20.90 lbs., 9.48 kg
Shipping Weight	23.40 lbs., 10.61 kg

**MATERIALS OF CONSTRUCTION**

I/O Copper Voice Coil	Die-cast Aluminum Basket
Fiberglass Former	X5 Cone Pulp
Neodymium Magnet	Advanced Polycotton Surround
Vented Motor	X5 Dust Cap Pulp





*From design and manufacturing to the stage or studio. Once you've experienced the performance of Eminence, you'll never accept anything else.*

## MISSION STATEMENT

*Eminence is dedicated to providing the best Quality, Value and Service to meet our customers' needs.*

## FOOTNOTES

- \* Please consult [www.eminence.com](http://www.eminence.com) for specifications of models with alternative impedances.
- \*\* Eminence Speaker LLC Tour Grade Drivers are power tested using the AES-1984 Testing Guidelines.
- \*\*\* The average output across the usable frequency range when applying 1W/1m into the nominal impedance. i.e: 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2 ft. x 2 ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Carver PM-120 amplifier | 2700 cu. ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).
- \*\*\*\* BETA 8CX, 10CX, and 12CX are coaxial speakers with tweeter sold separately. Published usable frequency response contingent upon use of ASD:1001 HF Driver.
- \*\*\*\*\* Multiple units exceeded published ratings evaluated under EIA-426A or AES specification while mounted on Eminence's H290, H290S, or H2EA horn in a non-temperature-controlled environment.
- \*\*\*\*\*The average on axis output across the entire usable frequency range when applying 1W/1m into the nominal impedance, i.e. 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft x 2ft baffle is built into the wall with horn front mounted | Carver PM-120 amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).

Prices, specifications and product cosmetics are subject to change without notice.

**EMINENCE SPEAKER LLC**

838 Mulberry Pike, Eminence, KY 40019



*Follow us:*

[EMINENCE.COM](http://EMINENCE.COM)

